

CP- VNC-T21ZR3-VMD

2 MP Full HD WDR Array Bullet Camera - 30Mtr.



Main Features

- 1/2.8" 2MP PS CMOS Image Sensor
- Max. 30fps@2MP(1920×1080)
- Ultra 265, H.265, H.264, MJPEG Triple-stream Encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR, Digital Defog, Corridor mode, ROI, AWB, AGC, BLC, HLC
- 2.8~12 mm Motorized Lens
- Array Range of 30 Mtrs, IP67, Micro SD Card, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS



Instastream

CE FC RoHS COMPLIANT

CP- VNC-T21ZR3-VMD

2 MP Full HD WDR Array Bullet Camera - 30Mtr.

Feature	Specification
Image Sensor	1/2.8" 2MP Progressive scan CMOS
Minimum Illumination	Colour: 0.002Lux (F1.6, AGC ON) 0Lux with IR
Shutter Speed	Auto/Manual, 1 ~ 1/100000s
White Balance	Auto/Manual
Lens	2.8~12 mm Motorized Lens
DORI Distance	2.8mm- 45 Detect (m) , 18 Observe (m), 9 Recognize (m), 4.5 Identify (m) 12mm- 192.9 Detect (m) , 77.1 Observe (m), 38.6 Recognize (m), 19.3 Identify (m)
Gain Control (AGC)	Auto/Manual
Video Compression	Ultra 265,H.265, H.264, MJPEG
S/N Ratio	>52dB
Angle of View	94.0° ~ 28°(H), 56.7°~14.4°(V), 122.2°~34.4°(O)
Back Light Compensation	BLC / HLC / WDR(120dB)
Video Streaming	Triple
Resolution	1920×1080
Frame Rate	Main Stream: 2MP (1920×1080): Max. 30 fps; Sub Stream: 2MP (1920×1080): Max. 30 fps; Third Stream: D1 (720×576): Max.30 fps
Motion detection	Up to 4 areas
Privacy Mask	Up to 8 areas
ICR	IR-cut filter with auto switch (ICR)
ROI	Up to 8 areas
Audio Input	impedance 35 kΩ; amplitude 2 V [p-p]
Audio Output	impedance 600 Ω; amplitude 2 V [p-p]
Audio Compression	G.711
Audio	Two-way audio Supported
Alarm IN	1 channel
Alarm Out	1 channel
Protocol	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, ONVIF (Profile S, Profile G, Profile T), API
Network Storage	ANR, NAS(NFS)
Ethernet	1 RJ45 10M/100M Base-TX Ethernet
IR	Array Range of 30 Mtr.

CP- VNC-T21ZR3-VMD

2 MP Full HD WDR Array Bullet Camera - 30Mtr.

Feature

OSD

Micro SD

Special Features

Operating Temperature

Humidity

Casing

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

Up to 8 OSDs

Micro SD, up to 256GB

Digital Defog

-35°C ~ +60°C (-31°F ~ 140°F)

≤ 95% RH (non-condensing)

Metal

12 V DC±25%, PoE (IEEE802.3 af)

Max 9W

IP67

253.4mm x 86mm x 71.7 mm (9.98" × 3.4" × 2.8")

1.0kg